IPC_D1202-B0007P79D1904 Release Notes

Zhejiang Uniview Technologies Co., Ltd

IPC_D1202-B0007P79D1904

Release Notes

Keywords: Version information, version upgrade

Abstract: This document provides detailed version information and upgrade procedure for

IPC_D1202-B0007P79D1904.

Acronym:

| Acronym | Full Name |
|---------|-----------|
| IPC | IP Camera |

Content

| 1 Version Information | 3 |
|---|----|
| 1.1 Version Number | 3 |
| 1.2 Release History ····· | 3 |
| 1.3 Version Mapping Table····· | 3 |
| 2 Feature Change Description | 4 |
| 3 Version Upgrade Description | 16 |
| 4 Version Upgrade Procedure ····· | 16 |
| 4.1 Upgrade Overview····· | 16 |
| 4.1.1 Version Upgrade Environment······ | 16 |
| 4.1.2 Version Upgrade Modes····· | 17 |
| 4.2 Upgrade Procedure ····· | 17 |
| 4.2.1 Upgrade Through the Web ······ | 17 |
| 5 Version Upgrade Disclaimer ······ | 17 |

1 Version Information

1.1 Version Number

IPC_D1202-B0007P79D1904

1.2 Release History

Table1Released versions

| Version No. | Basic Version No. | Released On | Remarks |
|-------------------------|-------------------------|-------------|------------------|
| IPC_D1202-B0007P79D1904 | IPC_D1202-B0007P77D1904 | 2022-04-22 | Improved release |

Table2 Version mapping table

| Product Mapping Item | Version No. (For External) |
|----------------------|----------------------------|
| NVR | B3328P36 |

1.3 Version Mapping Table

Table3Product models and corresponding versions

| Product Series | IPC Series | | |
|----------------|--|--|--|
| Series | IPC2122LR3、IPC2124LR3、IPC2125LR3、IPC2322LBR3、IPC2324LBR3、IPC322LR3、IPC3612LR3、IPC3614LR3、IPC3615LR3、IPC322SR3、IPC3232LR3、IPC3234LR3、IPC325LR3、IPC2122SR3、IPC、IPC2128LR3、SC | | |
| | IPC2122LR3 series:IPC2122LR3-PF40-D、IPC2122LR3-PF40M-D、 | | |
| | IPC2122LR3-PF60M-D、IPC2122LR3-PF40M-D、IPC2122LR3-PF60M-D、 | | |
| | IPC2122LR3-F40W-D、IPC2122LR3-PF28M-D、IPC2122LR3-S31、IPC2122LR3-S51 | | |
| | IPC2122LR3-S61、IPC2122LR3-S81、IPC2122LR3-M-S4、IPC2122LR3-M-S5 | | |
| | IPC2122LR3-M-S6 | | |
| | IPC2122SR3 series: IPC2122SR3-F40W-D、 | | |
| NA- dala | IPC2124LR3 series: IPC2124LR3-PF40M-D、IPC2124LR3-PF60M-D | | |
| Models | IPC2124LR3-PF28M-D、IPC2124LR3-F40W-D、IPC2124LR3-S31、IPC2124LR3-S51 | | |
| | IPC2124LR3-S61、IPC2124LR3-S81、IPC2124LR3-M-S4、IPC2124LR3-M-S5 | | |
| | IPC2124LR3-M-S6 | | |
| | IPC2125LR3 series: IPC2125LR3-PF40M-D、IPC2125LR3-PF60M-D | | |
| | IPC2125LR3 series:IPC2128LR3-S31、IPC2128LR3-S51 | | |
| | IPC2128LR3-S61、IPC2128LR3-S81、IPC2128LR3-M-S4、IPC2128LR3-M-S5 | | |
| | IPC2128LR3-M-S6 | | |

IPC2322LBR3 series: IPC2322LBR3-SP-D、IPC2322LBR3-SPZ28-D

IPC2324LBR3 series: IPC2324LBR3-SP-D、IPC2324LBR3-SPZ28-D

IPC322LR3 series:IPC322LR3-VSPF28-D、IPC322LR3-VSPF40-D

IPC322LR3-VSF28W-D

IPC3612LR3 series:IPC3612LR3-PF28-D、IPC3612LR3-PF40-D

IPC3614LR3 series:IPC3614LR3-PF28-D、IPC3614LR3-PF40-D

IPC3615LR3 series: IPC3615LR3-PF28-D、IPC3615LR3-PF40-D

IPC322SR3 series: IPC322SR3-VSF28W-D、IPC322SR3-VSF28W-D

IPC3232LR3 series: IPC3232LR3-VSP-D、IPC3232LR3-VSPZ28-D

IPC3234LR3 series: IPC3234LR3-VSP-D、IPC3234LR3-VSPZ28-D

IPC325LR3 series: IPC325LR3-VSPF28-D、IPC325LR3-VSPF40-D

IPC324LR3 series: IPC324LR3-VSPF28-D、IPC324LR3-VSPF40-D

IPC series: IPC-B114-PF28、IPC-B114-PF40、IPC-D114-PF28、

IPC-D114-PF40、IPC-T114-PF28、IPC-T114-PF40、IPC-D112-PF28

 $IPC-D112-PF40 \\ \\ \ IPC-T112-PF28 \\ \\ \ IPC-T112-PF40 \\ \\ \ IPC-B112-28 \\ \\ \ IPC-B112-40 \\ \\ \ IPC-$

IPC-B114-28、IPC-B114-40、IPC-T115-PF28-M、IPC-B124-PF28、

IPC-B124-PF40、IPC-T124-PF28、IPC-T124-PF40

IPC-B124-PF28-SC、IPC-B124-PF40-SC、IPC-T124-PF28-SC、IPC-T124-PF40-SC

IPC-B125-PF28-SC、IPC-B125-PF40-SC、IPC-T125-PF28-SC、IPC-T125-PF40-SC

IPC-B125-PF28、IPC-B125-PF40、IPC-T125-PF28、IPC-T125-PF40

SC series: SC-2643F-IZS, SC-3743F-IZS

Target file name

IPC_D1202-B0007P79D1904.zip

2 Feature Change Description

P79D1904(IPC_D1202-B0007P79D1904):

| Item | Feature | Description |
|----------------------|--------------------------|---|
| | Mandatory information | By default, user must fill in his/her mobile phone number |
| Newly added features | | or email address when logging in to the Web interface for |
| | | the first time. |
| Improved | None | None |
| features | | |
| Deleted | None | None |
| features | | 1.15.15 |

P77D1904(IPC_D1202-B0007P77D1904):

None

P75D1904

None

P73D1904

None

P72D1904

| Item | Feature | Description |
|-------------|-------------------|--|
| | New added models: | IPC-B124-PF28-SC、IPC-B124-PF40-SC、IPC-T124-PF28-SC |
| Newly added | | IPC-T124-PF40-SC、IPC-B125-PF28-SC、IPC-B125-PF40-SC |
| features | | IPC-T125-PF28-SC、IPC-T125-PF40-SC、IPC-B125-PF28 |
| | | IPC-B125-PF40、IPC-T125-PF28、IPC-T125-PF40 |
| Improved | None | None |
| features | | |
| Deleted | None | None |
| features | INOTIE | Notie |

P62D1904

| ltem | Feature | Description |
|-------------|-------------------|---|
| Newly added | New added models: | IPC-B122-PF28、IPC-B122-PF40、IPC-T122-PF28、IPC-T122-PF40 |
| features | | IPC-B124-PF28、IPC-B124-PF40、IPC-T124-PF28、IPC-T124-PF40 |
| Improved | None | None |
| features | | |
| Deleted | None | None |
| features | None | Notie |

P61D1904

None

P37D1904

| Item | Feature | Description |
|----------------------|-------------------|-----------------|
| Newly added features | New added models: | IPC-T115-PF28-M |
| Improved features | None | None |
| Deleted features | None | None |

P30D1904

| Item | Feature | Description |
|-------------------------|-----------------------------|---|
| Newly added features | Sync time with cloud server | (1)Set Sync Mode to Sync with Cloud Server in time settings. The configuration takes effect only when the device gets online on EZCloud. (2)After being disconnected from power (which restores the device time to 2011), the device syncs time with the cloud server after restarts and gets online on EZCloud. (3)The device syncs time with the cloud server when time zone or DST is configured on its Web interface or EZView. (4)The device syncs time with the cloud server every 30 minutes. (Available for Wi-Fi products only.) |
| Deleted features | None | None |

P20D1904

| Item | Feature | Description |
|----------------------|-------------------------|---|
| | Stream scramble | Encrypt video content to improve security. After stream scramble is enabled on the Web interface or the managing NVR, live view is only available on its Web interface or the NVR.(Available for Wi-Fi kit only. NVR version: GNVRV300R004B01D012SP69.) |
| Newly added features | Wi-Fi cascade | Add Wi-Fi cascade mode for Wi-Fi products.(Available for Wi-Fi kit only. NVR version: GNVRV300R004B01D012SP69.) |
| | Human body detection | In human detection mode, an alarm will be triggered when a human appears in the configured area, and the human body will be highlighted by a rectangular green box in live view. |
| | WDR | Easy series cameras support auto WDR mode. |
| Deleted features | None | None |

P10D1904:

| Item | Feature | Description |
|-------------------------|--------------------------|---|
| | PPPoE | Display the obtained IP address in PPPoE mode. |
| | SD Card | Support image storage to SD card: 1. By default, 20% of the SD card capacity is allocated for image storage. 2. Support the storage of scheduled snapshots and snapshots taken at set interval. 3. Support the storage of alarm triggered snapshots. 4. In Photo page, snapshots and smart snapshots are |
| Newly added features | Port mapping | displayed in different directories. Add manual port mapping 1. Mapping mode includes UPnP and Manual. 2. The UPnP mapping mode includes Auto and Manual. The port cannot be configured in Auto UPnP mapping mode. 3. If the mapping mode is Manual, only port configurations are displayed. 4. If port mapping is disabled, all configurations will be hidden. |
| | Functions without plugin | Support H.265 video and G.711U audio without plugin. Display the status such as server status, SD card status, and port mapping status when the camera is operated on another web client. |
| Improved features | Running time | Support clearing the accumulated running time of the camera on NVR. |
| | Power | Increase Wi-Fi transmit power, with signal strength improved. |
| Deleted features | None | None |

P30D1812:

| Item | Feature | Description |
|----------------------|-------------------|--|
| Newly added features | New added models: | IPC2124LR3-F40W-D |
| Improved | Log | Includes IR cut switch count in logs to facilitate judgment on |
| features | | its service life. |
| Deleted | None | None |
| features | None | None |

P20D1812:

| Item | Feature | Description |
|-------------|-------------------|---|
| Newly added | New added models: | IPC-D114-PF28、IPC-D114-PF40、IPC-T114-PF28、IPC-T114-PF40 |
| features | | |
| Improved | None | None |
| features | | |
| Deleted | None | None |
| features | None | Notie |

P10D1812:

| Item | Feature | Description |
|----------------------|-----------------------------|--|
| | Illegal login lock | Add illegal login lock on the Web interface. When enabled, the account will be locked after 5 consecutive wrong passwords. |
| | NTP server port | NTP server port configurable. |
| | SDDP | Add SDDP and Identify settings in Demo page. |
| | Refresh Storage page | Storage page refreshes after the storage medium is formatted. |
| Newly added features | English/Chinese language | Distribution products support English/Chinese language switch. |
| | Wi-Fi channel | Add channel 14 for Wi-Fi devices to improve anti-jamming performance: |
| | | In Wi-Fi mode, the camera can connect to channel 14 network; |
| | | In Wi-Fi Hotspot mode, the camera can be set as a channel 14 hotspot for other devices. |
| Improved features | Intelligent snapshot | The resolution of intelligent functions triggered snapshots can be configured. |
| Deleted features | None | None |

P31D1809:

| ltem | Feature | Description |
|-------------------------|-----------------------|--|
| | Intelligent functions | Add intrusion detection for Easy series fixed dome and bullet cameras |
| Newly added features | Read QR code | Wi-Fi device in default settings can connect to the same Wi-Fi as the mobile phone by reading the QR code displayed on EZView. The IR indicator shows connection status: 1. The IR indicator lights up and remains lit: The camera is starting up. 2. The IR indicator flashes slowly (around once every second): The camera has finished startup and is ready for Wi-Fi connection. 3. The IR indicator flashes quickly (around once every 0.3s): Wi-Fi connection failed. 4. The IR indicator turns off: Wi-Fi connection succeeded. |
| Dewarping | Dewarping | Add dewarping function |
| Improved features | None | None |
| Deleted features | None | None |

| New added | IPC322LR3-VSF28W-D、IPC2122LR3-F40W-D、IPC2122LR3-PF28M-D、 |
|-----------|--|
| models | IPC2124LR3-PF28M-D、IPC322SR3-VSF28W-D、IPC2122SR3-F40W-D |

P20D1809:

None.

P10D1809

| Item | Feature | Description |
|-------------------------|--|--|
| Newly added features | Alarm report to EZVMS over WAN | Alarm report to EZVMS over the WAN. |
| | Old password required when changing password | Old password is required when changing user password. |
| | SSL certificate signature algorithm change | The signature algorithm for SSL certificate changes from SHA-1 to SHA-2. |
| | QoS | Support QoS. |
| | Open source software licenses | Add open source software licenses on the Basic Info page of Web interface. |
| Improved features | Record IP and port of operation source in logs | When configuring or managing IPC on platform, NVR or IPC Web interface, the IP address and port number of the operation source will be recorded in IPC logs. |
| Deleted features | None | None |

| New | IPC2122SR3-F40W-D、IPC2124LR3-PF40M-D、IPC2124LR3-PF60M-D、 |
|--------|--|
| added | IPC2125LR3-PF40M-D、IPC2125LR3-PF60M-D、IPC2322LBR3-SP-D、 |
| models | IPC2322LBR3-SPZ28-D、IPC2324LBR3-SP-D、IPC2324LBR3-SPZ28-D、 |
| | IPC3614LR3-PF28-D、IPC3614LR3-PF40-D、IPC3615LR3-PF28-D、IPC3615LR3-PF40-D、 |
| | IPC322SR3-VSF28W-D、IPC3232LR3-VSP-D、IPC3232LR3-VSPZ28-D、 |
| | IPC3234LR3-VSP-D、IPC3234LR3-VSPZ28-D、IPC325LR3-VSPF28-D、 |
| | IPC325LR3-VSPF40-D、IPC324LR3-VSPF28-D、IPC324LR3-VSPF40-D |

P30D1806

None.

P20D1806

| ltem | Feature | Description |
|----------------------|----------------|--|
| Newly added features | Privacy policy | Show privacy policy at user's first login. |
| Improved features | None | None |
| Deleted features | None | None |

P10D1806

| Item | Feature | Description |
|----------------------|---|--|
| Newly added features | Onvif Profile T | Profile T supported. |
| Improved features | Add device by scanning without cloud account | With a strong device password, Quick Add allows you to add device by scanning QR code without a cloud account. |
| | Improved people counting&face detection configuration | In people counting configuration, the improved interface allows you to set the max. /min. object size by drawing. Inface detection configuration, the improved interface allows you to set themin. pupillary distance by drawing. |
| Deleted features | None | None |

D1806

| Item | Feature | Description |
|----------------------|--------------------------------------|---|
| Newly added features | None | None |
| | Four-corner frame for face detection | The face detection frame is changed from full frame to four-corner frame. |
| Improved features | Add condition of use for U-Code | When the capture mode is more than 30 frames per sec, U-Code cannot be configured for main stream, sub stream and third stream. |
| | More live view channels | Up to 35 concurrent live view windows are supported on the same PC. |
| Deleted features | Delete face tracking line | After enabling face detection and intelligent mark, the target is tracked by detection frame, with the tracking line deleted. |

P30D1803

None.

P20D1803

| Item | Feature | Description |
|-------------------------|--------------------------|---|
| Newly added features | Live view without plugin | Play H.264 video without plug-in. |
| | New port mapping type | Added the HTTPS port on the port mapping page . |
| | New protocol | SNMP |
| Improved | SD card recording | Fast forward/rewind, and control progress by dragging the |
| features | playback | timeline . |
| Deleted features | None | None |

P10D1803

| Item | Feature | Description |
|----------------------|--------------------|--|
| | New smart features | Object left behind and object removed. |
| Newly added features | New added models: | IPC2122LR3-PF40M-D、IPC2122LR3-PF60M-D、 |
| leatures | | IPC322LR3-VSPF28-D、IPC322LR3-VSPF40-D、 |
| | | IPC3612LR3-PF28-D、IPC3612LR3-PF40-D |
| Improved | Snapshot | Snapshot resolution selectable. |
| features | resolution | Shapshot resolution selectable. |
| Deleted features | Duration | Deleted the Duration parameter from the Motion Detection |
| | | page. |
| | Original Image | Original Image Clarity is deleted from image parameters. |
| | Clarity | Original image clarity is deleted from image parameters. |

3 Version Upgrade Description

None.


4 Version Upgrade Procedure

4.1 Upgrade Overview

4.1.1 Version Upgrade Environment

1. Network Architecture for Upgrade

Figure1Network architecture



As shown in this figure, the version files are stored on the PC that is connected to the IPCs through the network.

4.1.2 Version Upgrade Modes

You can upgrade through the Web.

4.2 Upgrade Procedure

4.2.1 Upgrade Through the Web

- (1) Log in to the Web interface as **admin** (default password: 123456).
- (2) Click Setup>Maintenance>Device Maintenance. The Device Maintenance page is displayed.



- (3) Click **Browse** in the **Firmware Upgrade** area. In the **Select** dialog box that appears, select the upgrade file package, for example, IPC_D1202-XXXXX.zip, and then click **Open.**
- (4) Click **Upgrade**. You cannot operate on other pages during the upgrade process.
- (5) Wait till the upgrade is completed. A message appears to indicate successful upgrade and prompt you to log in again after the device restarts.

5 Version Upgrade Disclaimer

- By setting or installing this program in any way you agree to all of the following terms and conditions. Your
 downloading or using the program means you acknowledge your full understanding and acceptance of the
 following terms and conditions. If you do not agree to any of the following terms, you shall not use the program
 and you must cease installing and delete the program immediately.
- 2. The upgrade program is only applicable to the intended regions and product models. Before upgrade or update, please read the release notes carefully to make sure the program is applicable to your region and product model. You will be fully liable and responsible for all the consequences of device abnormality and related maintenance

- costs caused by your improper operations.
- 3. Uniview owns or is legally authorized to own all rights and IPRs (Intellectual Property Rights) of the program and the supplied release notes.
- 4. Software upgrades are for the optimization of product functions and do not mean there is defect.
- 5. You must strictly follow instructions in the release notes during the upgrade process, otherwise you are responsible for the possible consequences and related maintenance costs.
- 6. You shall not engage in any of the following activities, otherwise you would be liable for infringement and responsible for any adverse consequences arising therefrom.
- 6.1 Copy the program (exclude the reasonable and necessary copies for internal backups);
- 6.2 Exclude this statement when using the program or transfer the program to any third party;
- 6.3 Modify the program or its derivatives;
- 6.4 Reverse engineer, decompile or disassemble this program.
- 7. The program is only intended for authorized users. Its architecture, organization and source code are valuable trade secrets and confidential information owned by Uniview and its authorized parties. You agree not to provide or disclose any confidential information contained in or derived from the software to any third party. No part of this document may be excerpted, reproduced, or distributed in any form by any entity or individual without written consent from our company.